



## 1-1/4" Foam Dielectric, LDF Series – 50-ohm

### LDF6-50

Description	Type No.
<b>Cable Ordering Information</b>	
<b>Standard Cable</b>	
1-1/4" Standard Cable, Standard Jacket	LDF6-50
<b>Fire Retardant Cable</b>	
1-1/4" Fire Retardant Jacket (CATVR)	LDF6RN-50
<b>Low VSWR and Specialized Cables</b>	
1-1/4" Low VSWR, specify operating band	LDF6P-50-(**)

\*\* Insert suffix number from "Low VSWR Specifications" table, page 515

#### Characteristics

Electrical	
Impedance, ohms	50 ± 1
Maximum Frequency, GHz	3.3
Velocity, percent	89
Peak Power Rating, kW	205
dc Resistance, ohms/1000 ft (1000 m)	
Inner	0.22 (0.72)
Outer	0.19 (0.62)
dc Breakdown, volts	9000
Jacket Spark, volts RMS	10000
Capacitance, pF/ft (m)	22.9 (75.1)
Inductance, µH/ft (m)	0.056 (0.184)
Mechanical	
Outer Conductor	Copper
Inner Conductor	Copper
Diameter over Jacket, in (mm)	1.55 (39.4)
Diameter over Copper Outer Conductor, in (mm)	1.41 (35.8)
Diameter Inner Conductor, in (mm)	0.516 (13.1)
Nominal Inside Transverse Dimensions, cm	3.11
Minimum Bending Radius, in (mm)	15 (380)
Number of Bends, minimum (typical)	15 (40)
Bending Moment, lb-ft (N·m)	36 (49)
Cable Weight, lb/ft (kg/m)	0.63 (0.94)
Tensile Strength, lb (kg)	1300 (590)
Flat Plate Crush Strength, lb/in (kg/mm)	125 (2.2)

#### Attenuation and Average Power

Frequency MHz	Attenuation dB/100 ft	Attenuation dB/100 m	Average Power, kW
0.5	0.017	0.056	175.0
1	0.024	0.079	123.0
1.5	0.030	0.097	101.0
2	0.034	0.112	87.1
10	0.077	0.253	38.6
20	0.110	0.361	27.1
30	0.135	0.444	22.0
50	0.176	0.579	16.9
88	0.237	0.778	12.6
100	0.254	0.832	11.7
108	0.264	0.867	11.3
150	0.314	1.03	9.47
174	0.340	1.12	8.75
200	0.367	1.20	8.12
300	0.457	1.50	6.52
400	0.535	1.76	5.57
450	0.571	1.87	5.22
500	0.606	1.99	4.92
512	0.614	2.01	4.86
600	0.671	2.20	4.44
700	0.732	2.40	4.07
800	0.789	2.59	3.78
824	0.803	2.63	3.71
894	0.841	2.76	3.54
960	0.876	2.87	3.40
1000	0.897	2.94	3.32
1250	1.02	3.35	2.92
1500	1.14	3.73	2.62
1700	1.22	4.02	2.43
1800	1.27	4.16	2.35
2000	1.35	4.43	2.21
2100	1.39	4.56	2.14
2200	1.43	4.69	2.08
2300	1.47	4.82	2.03
3000	1.73	5.68	1.72
3300	1.84	6.02	1.62

#### Standard Conditions:

For Attenuation. VSWR 1.0, ambient temperature 20°C (68°F).

For Average Power. VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F); no solar loading.