



# 7/8" Flexible Feeder, Foam Dielectric VXL Series – 50-ohm



HELIAX® Coaxial Cables

## VXL5-50

Description	Type No.
<b>Cable Ordering Information</b>	
<b>Standard Cable</b>	
7/8" Standard Cable, Standard Jacket	VXL5-50
<b>Fire Retardant Cable</b>	
7/8" Fire Retardant Jacket (CATVR)	VXL5RN-50
<b>Low VSWR Cables</b>	
7/8" Low VSWR, specify operating band	VXL5P-50-(**)
<b>Jumper Cable Assemblies - See page 584</b>	
**Insert suffix number from "Low VSWR Specifications" table, page 504	
<b>Characteristics</b>	
<b>Electrical</b>	
Impedance, ohms	50 ± 1
Maximum Frequency, GHz	4.9
Velocity, percent	88
Peak Power Rating, kW	90
dc Resistance, ohms/1000 ft (1000 m)	
Inner	0.82 (2.70)
Outer	0.36 (1.19)
dc Breakdown, volts	6000
Jacket Spark, volts RMS	8000
Capacitance, pF/ft (m)	22.6 (74.2)
Inductance, µH/ft (m)	0.06 (0.197)
<b>Mechanical</b>	
Outer Conductor	Copper
Inner Conductor	Copper Tube
Diameter over Jacket, in (mm)	1.08 (27.5)
Diameter over Copper Outer Conductor, in (mm)	0.98 (24.9)
Diameter Inner Conductor, in (mm)	0.371 (9.42)
Minimum Bending Radius, in (mm)	5 (125)
Number of Bends, minimum (typical)	15 (40)
Bending Moment, lb-ft (N·m)	12 (16.3)
Cable Weight, lb/ft (kg/m)	0.29 (0.43)
Tensile Strength, lb (kg)	225 (102)
Flat Plate Crush Strength, lb/in (kg/mm)	80 (1.4)

### Attenuation and Average Power

Frequency MHz	Attenuation dB/100 ft	Attenuation dB/100 m	Average Power, kW
0.5	0.027	0.089	90.0
1	0.038	0.126	68.5
1.5	0.047	0.154	55.9
2	0.054	0.178	48.4
10	0.122	0.402	21.5
20	0.174	0.571	15.1
30	0.214	0.702	12.3
50	0.278	0.911	9.47
88	0.372	1.22	7.07
100	0.397	1.30	6.62
108	0.413	1.36	6.36
150	0.491	1.61	5.36
174	0.530	1.74	4.96
200	0.571	1.87	4.61
300	0.707	2.32	3.72
400	0.825	2.71	3.19
450	0.878	2.88	2.99
500	0.930	3.05	2.83
512	0.942	3.09	2.79
600	1.03	3.37	2.56
700	1.12	3.66	2.36
800	1.20	3.94	2.19
824	1.22	4.01	2.16
894	1.28	4.19	2.06
960	1.33	4.36	1.98
1000	1.36	4.46	1.94
1250	1.54	5.05	1.71
1500	1.71	5.60	1.54
1700	1.83	6.01	1.44
1800	1.89	6.21	1.39
2000	2.01	6.59	1.31
2100	2.07	6.78	1.27
2200	2.12	6.97	1.24
2300	2.18	7.15	1.21
3000	2.54	8.35	1.04
3400	2.74	8.99	0.961
4000	3.02	9.90	0.873
4900	3.41	11.2	0.772

#### Standard Conditions:

For Attenuation, VSWR 1.0 ambient temperature 20°C (68°F).

For Average Power, VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F), no solar loading.